

StraPack **AQ-7MV18**

AUTOMATIC STRAPPING MACHINE



Easy strap loading



Up to 30 strap cycles/minute



Robust, stainless steel construction



Ready to operate in just 25 seconds



Ideal when operating in moisture laden food processing environment such as meat, poultry and seafood. The stainless steel StraPack AQ-7MV18 automatic strapping machine features a fully enclosed cabinet which protects the components from water and spray.

FEATURES & BENEFITS

Stainless Steel Construction

Fully enclosed control cabinet and reinforced lower cabinet protect against moisture.

Side Seal Design

Side Seal Design helps protect against salt water run-off, oil and debris.

Permanently Lubricated Mechanisms

Self-lubricating design reduces wear and tear and increases operational life.

Portable & Versatile

Locking castors and Adjustable table height to 3 positions (730mm, 750mm, 770mm).

Easy Tension Control

Tension is adjusted via a convenient dial. Tension arm maintains consistent tension.

Reliable Motor & Drive Mechanism

Designed with a minimum of moving parts to increase motor life and reduce maintenance requirement.

Dimensions	Width	1580 mm
	Depth	610 mm
	Height	1782 mm
	Weight	200 kg
Table Height	730mm, 750mm or 770mm	
Sealing Height	810 mm	
Arch Width/ Height	700 mm / 485mm (+/- 20mm)	
Min Package Size	W 30 x H 80 mm	
Max Package Size	W 680 x H 500 mm	
Joint / Strap / Coil	Heat Seal/ Polypropylene/ ID 200 x OD 450 x W 200 mm	
Strap Width	9, 12 mm	
Strap Tension	Up to 450N (46kgf), 150mm stroke	
Strapping Rate	2.0 seconds	
Power Supply	380-415 V - 3 Phase 50 Hz 0.85 KVA	



Gordian House, Brunel Road, Houndmills Industrial Estate, Basingstoke, Hampshire RG21 6XX, UK.



www.gordianstrapping.co.uk



01256 394444



sales@gordianstrapping.com