



StraPack

StraPack SQ-800

AUTOMATIC STRAPPING MACHINE



High speed - up to 54 straps per minute




Ready to operate in less than 25 seconds



Robust, portable design with locking castors



Foot bar and adjustable height as standard



FEATURES & BENEFITS

Dedicated DC Tension Motor Less wear parts (i.e. interlock shaft, tension, pulley) = improved speed and quieter operation.

Foot Bar Easy-to-operate foot bar enables faster, twohanded operation

Height can be set to 8 positions from floor level for Adjustable Table Height

easy integration into existing packaging lines: 794,

809, 824, 839, 854, 869, 884 & 899 mm.

Self-lubricating design reduces wear and tear and Easy Maintenance

increases operational life.

Easy Strap Loading Strap loading is as easy as a touch of a lever. There

is no need to thread the strap.

If the SQ-800 is operated without a package on Anti Jam Function

> the table, the strap forms a small loop which is ejected from the sealing unit. The machine then

re-feeds ready for the next cycle.

Auto Re-Feed In case of a feeding issue, the machine will re-feed

the strap automatically

Advanced Heater Design SQ-800 is ready to operate in less than 25 seconds,

contributing to increased packaging line

efficiencies.

Variable Tension A wide range of tension is available via a digitally

> controlled tension dial. Tension capability is up to 46kgf (equivalent of 150mm stroke). Unlike many other machines in the market, tension does not

compromise the cycle speed.

Dimensions	Width	1254 mm
	Depth	609 mm
	Height	1403-1508 mm
	Weight	146 kg
Table Height	794, 809, 824, 839, 854, 869, 884, 899 mm	
Min Package Size	W 80 x H 30 mm	
Max Package Size	W 620 x H 480 mm	
Joint/Strap/Coil	Heat Seal/Polypropylene/ID 200 x OD 450 x W 200 mm	
Strap/Width/ Thickness	5, 6, 9, 12, 15.5 mm	
Strap Tension	Up to 450N (46kgf), 150mm stroke	
Power Supply	100 - 240V - Single phase 50/60Hz 0.74kVA	









01256 394444

