

StraPack **SQ-800S**

AUTOMATIC STRAPPING MACHINE



Ideal for strapping small bundles



High speed - up to 54 straps per minute
(even with tension applied)



Ready to operate in less than 25 seconds



Foot bar and adjustable height as standard



The latest generation automatic strapping machine from StraPack is specifically designed for small bundles such as bundles of wood, pipes, rods, mouldings etc.

FEATURES & BENEFITS

Dedicated DC Tension Motor

Less wear parts (i.e. interlock shaft, tension, pulley)
= improved speed and quieter operation.

Foot Bar

Easy-to-operate foot bar enables faster, two-handed operation

Adjustable Table Height

Height can be set to 8 positions from floor level for easy integration into existing packaging lines: 794, 809, 824, 839, 854, 869, 884 & 899 mm.

Cycle Counter

Easy-to-operate foot bar enables faster, two-handed operation.

Easy Strap Loading

Strap loading is as easy as a touch of a lever. There is no need to thread the strap.

Easy Maintenance

Self-lubricating design reduces wear and tear and increases operational life.

Anti Jam Function

If the SQ-800S is operated without a package on the table, the strap forms a small loop which is ejected from the sealing unit. The machine then re-feeds ready for the next cycle.

Auto Re-Feed

In case of a feeding issue, the machine will re-feed the strap automatically

Advanced Heater Design

SQ-800 is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

Variable Tension

A wide range of tension is available via a digitally controlled tension dial. Tension capability is up to 46kgf (equivalent of 150mm stroke). Unlike many other machines in the market, tension does not compromise the cycle speed.

Dimensions	Width	1254 mm
	Depth	609 mm
	Height	1304-1409 mm
	Weight	139 kg
Table Height	794, 809, 824, 839, 854, 869, 884, 899 mm	
Min Package Size	Wood: W 40mm x H 30mm, Ø Pipe: 30mm x2	
Max Package Size	W 620 x H 380 mm	
Joint / Strap / Coil	Heat Seal/ Polypropylene/ ID 200 x OD 450 x W 200 mm	
Strap / Width / Thickness	5, 6, 9, 12, 15.5 mm	
Strap Tension	Up to 450N (46kgf), 150mm stroke	
Power Supply	100 - 240V - Single phase 50/60Hz 0.74kVA	



Gordian House, Brunel Road, Houndmills Industrial Estate, Basingstoke, Hampshire RG21 6XX, UK.



www.gordianstrapping.co.uk



01256 394444



sales@gordianstrapping.com