



## StraPack D-53PLT2

## SEMI-AUTOMATIC STRAPPING MACHINE



Compatible with PP strap




Sealing Point 340mm from floor for lower pallets



Portable design with fold up sword



Battery/Mains or Mains only models



## **FEATURES & BENEFITS**

Versatile Tension Capability

Manual tension or automatic tension mode can be easily selected by the operator. In manual mode, tension can be controlled via the operations bar. This is particularly helpful if corner edge protectors are being applied to the pack. In automatic mode, tension is applied at the preselected level.

Battery/Mains or Mains Only Mode

Two models available: D-53PLT2B (Battery/Mains) and D-53PLT2 (Mains only)

4-way Pallet Entry Sword (aka bayonet) height can be adjusted easily

(10 mm, 22.5 mm & 35 mm) by a lever to allow the sword to enter the pallet voids from two different

directions and cross strap the pallets.

Lower Sealing Point for Small

**Pallets** 

Sealing point is only 340 mm from the floor so that can lower pallets can also be strapped.

Robust & Portable Heavy duty metal castors allow for the machine to

be quickly installed or moved to any single-phase supply outlet. Sword folds up for easy and safe

storage.

Variable Tension Range of tension settings (up to 70kgf) available

via a single tension dial.

Dimensions	Width	2195mm (1000 when sword is folded)
	Depth	1208 mm
	Height	542 mm
	Weight	90 kg
Sword Height	10, 22.5, 35 mm	
Min Package Size	W 400 mm x H free	
Joint/Strap/Coil	Heat seal/ Polypropylene/ ID 200 x OD 450 x W 200 mm	
Strap Width	12 mm	

240V 1 Phase 50/60 Hz 0.65 KVA 0.4kw



Strap Tension

**Power Supply** 



9-70 kgf







01256 394444



sales@gordianstrapping.com