

# OMS TS300 BRICK STATION

## FULLY AUTOMATED VERTICAL PALLET STRAPPING MACHINE



Compresses, vibrates and vertically straps blades of bricks



200,000 cycles between services with OMS Strapping Heads



Applies edge protection prior to strapping on all 4 corners of the pack



Telescopic Arch tracks maximise production performance



OMS TS300 machines incorporating TR19HT heads are used in brick and tile strapping applications where the heads are lowered and seals are formed on the tops of the packs.

## FEATURES & BENEFITS

### Pack Compression

Compression and vibration throughout the strapping cycle ensures a uniform, tight pack.

### Edge Protection Applicators

Tape dispensers with out of tape sensors, guide pulleys and punches ensure each pack has correct length of edge protection.

### Telescopic Arch Tracks

Telescopic tracks reduce travel of the strapping head and wear on the lift motor and guides, thereby maximising production performance.

### Proven & Reliable Heat Seal Strapping Heads

OMS TR Series Heads only require servicing every 200,000 cycles.

### Fast, Consistent Strap Feed

Precise, repeatable strap feeding avoids jams and increases up-time.

### Strap Coil Holder Options

Options include Tower, Scissor and Jumbo Coil Holders, all with auto recovery to ensure strap is taut and controlled.

### Optional Equipment

Include: Mobile Strapping head(s), Pedestal or Desk Control Panel, integrated conveyor with optional Centering device, stabilizing top press, powered take off conveyor, turntables and cross transfer conveyors.

### Safety Guarding Options

Gordian can offer a full perimeter safety guarding system in partnership with our safety system suppliers.

Dimensions	Width	5650 mm
	Depth	3555 mm
	Height	3360 mm
Standard Conveyor Dimensions	720 mm H X 860 mm W	
Pack Height	Min. 700mm to Max. 1100mm	
Strap / Coil Options	Polyester - ID 406mm x W 150mm	
Strap Width	12-19mm - TR19HT Strapping Head	
Strap Tension	0 to 700kg dependent on head	
Cycle Time	12 seconds per cycle or 5 straps / min.	
Tensioning Speed	0.25 m/sec	
Strap feeding and recovery speed	2.7 m/sec	
Power Supply	230 / 400V, 50 / 60Hz	
Noise Level	<70Db	



Gordian House, Brunel Road, Houndmills Industrial Estate, Basingstoke, Hampshire RG21 6XX, UK.



[www.gordianstrapping.co.uk](http://www.gordianstrapping.co.uk)



01256 394444



[sales@gordianstrapping.com](mailto:sales@gordianstrapping.com)