



StraPack RQ-7000M18

FULLY AUTOMATED STRAPPING MACHINE



Automatic strap loading



High speed – 50 straps/minute



Robust, stainless steel construction



Ready to operate in less than 20 seconds

The corrosion-free StraPack RQ7000MVI8 fully automated strapping machine is manufactured from stainless steel and waterproof materials. It's ideal in moisture-laden food processing environments such as meat, fish and poultry.

FEATURES & BENEFITS

Useful Features The RQ-7000MV18 boasts the advanced high-

speed sealing head of the RQ7000 and many features of the RQ-8 such as strap self-loading, re-

feed and loop ejection.

Moisture Protection Features Stainless steel construction, fully enclosed cabinet,

side sealing design, reinforced lower cabinet,

permanently lubricated mechanisms.

Self-Loading Strap Automatic, self-loading strap eliminates

complicated manual threading.

High Speed

The high speed sealing head can strap up to 50 traps/minute without compromising strap tension. The RQ-7000MV18 is ready to operate in less than 20 seconds, meaning more up time.

Dimensions	Width	1580 mm
	Depth	610 mm
	Height	1772 mm
	Weight	220 kg
Table Height	620, 640, 660 mm	
Sealing Height	810 mm	
Arch Size	W 490 mm x H 650 mm	
Conveyor Height	710 - 1390 mm	
Conveyor Speed	up to 60 m/ min	
Minimum Package Size	W 30 x H 80 mm	
Maximum Package Size	W 475 x H 475 mm	
Air Requirements	31.7 l/min (ANR) / 0.4MPA (57psi)	
Strap Width	5, 6 mm as standard	
Strap Tension	Max 392N (40kgf), 150mm Stroke	
Power Supply	200-240V 380-480V	











01256 394444

