

StraPack RQ-8CR/FB

FULLY AUTOMATED STRAPPING MACHINE



Easy strap loading



Ready to operate in less than 25 seconds



Compression Unit can easily be activated or deactivated



Compatible with Conveyor Speeds of up to 30m/ min

FEATURES & BENEFITS

Self-Correcting Technology

Any forwarding failure is automatically re-attempted up to 3 times. If re-feeding is unsuccessful, the machine automatically stops and activates a warning light.

Self-Diagnostic Function

Programmable microprocessor constantly monitors critical functions. Any irregularity is immediately displayed.

Variable Tension

A wide range of tension can be selected via a single dial. Tension capability up to 80kg.

Programmable Photocell

Enables multiple strap operations at different positions on the pack.

Reliable Motor & Drive Mechanism

Self-lubricating design and minimal moving parts reduces wear & tear and increases operational life.

Energy Saving Auto Shut-Off

Machine enters standby mode after 3 minutes - thereby saving energy.

Dimensions	Width	2259 mm
	Depth	611 mm
	Height	2198 mm
	Weight	400 kg
Arch Size	W 1650 mm x H 500 mm	
Conveyor Height	1081 mm	
Minimum Package Size	W 200 x H 120 mm L 300mm	
Maximum Package Size	W 1590 x H 430 mm	
Joint / Strap / Coil	Heat Seal/ Polypropylene/ ID 200 x OD 450 x W 200 mm	
Strap Width	5, 6 mm as standard	
Strap Tension	up to 80 kg stroke 150 mm	
Power Supply	200, 220, 240, 380, 400, 415, 440, 480V 3 phase 50/60Hz 0.83KVA	

Conveyor Speed Information

Inverter Cycle	Conveyor Speed (per min)
20 Hz	9.8 m
30 Hz	14.7 m
40 Hz	19.6 m
50 Hz	24.5 m
60 Hz (Max)	29.4 m

Max Package Weight	Max Conveyor Speed (per min)
20 kg	30 m
25 kg	24 m
30 kg	20 m
35 kg	17 m
40 kg	15 m



Gordian House, Brunel Road, Houndmills Industrial Estate, Basingstoke, Hampshire RG21 6XX, UK.



www.gordianstrapping.co.uk



01256 394444



sales@gordianstrapping.com