



OMS IS43

FULLY AUTOMATED STRETCH HOODING MACHINE



Reliable mechanical bag opening process



Easy integration over existing conveyors



Film loading and maintenance at ground level



Film reel holders with driven air mandrels



FEATURES & BENEFITS

Versatile Hooding Options

Applies caps, sleeves or full hoods with ears flush to the pack.

Easy Integration over Existing Conveyors

Can be installed over existing conveyors without modifications. Pack or Pallet lifting device may be

required.

Driven Film Reel Holder(s) with Air Mandrels

Motorized air mandrels eliminate core slippage and mitigate the effects of film blocking. They can

support steel, plastic or cardboard cores up to

500kg.

Mechanical Bag Opening

Mechanical fingers open each and every bag regardless of static build up, meaning no bags are

wasted.

Motorized Film Stretch Process Stretch group is opened by synchronized motor and gearbox drives, rather than complex, noisy, hydraulic systems with potential for leaks.

Easy Film Reel Changeover

New film is easily threaded into the film clamps.

Extractable film carriage is standard for machines

with 2 or more reel holders.

Ground Level Film Loading & Eliminates risks involved with working at height. Maintenance

Optional Equipment Pedestal or Desk Control Panel, Driven Conveyors,

Centering Device, Pack Lifting, Film-End Signal, Mark Reader, Pack Height Detection Device.

Safety Guarding Options Gordian can offer a full perimeter safety guarding

system in partnership with our safety system

suppliers.

Film	Stretch Polyethylene
Film Thickness	50-150 micron
Reel Diameter	Up to 1000mm
Reel Max. Weight	500kg
Production Speed	Up to 120 pallets/hr
Pallet Dims (Small, Medium & Large)	750 x 750 mm, 1300 x 1300 mm, 1600 x 1600 mm
Air Pressure	5.5 – 7bar
Air Consumption	100 NI/cycle approx.
Power Supply	230/400V,50/60Hz









01256 394444

