



StraPack SQ-800Y

AUTOMATIC STRAPPING MACHINE



High speed - up to 50 straps per minute




Ready to operate in less than 25 seconds



Robust, portable design with locking castors



Easily fits into conveyor systems



FEATURES & BENEFITS

Dedicated DC Tension Motor

Less wear parts (i.e. interlock shaft, tension, pulley)

= improved speed and quieter operation.

Easy Maintenance Self-lubricating design reduces wear and tear and

increases operational life.

Easy Strap Loading Strap loading is as easy as a touch of a lever. There

is no need to thread the strap.

Auto Re-Feed In case of a feeding issue, the machine will re-feed

the strap automatically



Anti Jam Function If the SQ-800Y is operated without a package on

> the table, the strap forms a small loop which is ejected from the sealing unit. The machine then

re-feeds ready for the next cycle.

Advanced Heater Design SQ-800Y is ready to operate in less than 25

seconds, contributing to increased packaging line

efficiencies.

Variable Tension A wide range of tension is available via a digitally

controlled tension dial. Tension capability is up to 46kgf (equivalent of 150mm stroke). Unlike many other machines in the market, tension does not

compromise the cycle speed.

Standard Specifications (arch size W 600 X H 850 mm)

Dimensions	Width	1500 mm
	Depth	610 mm
	Height	1723 mm
	Weight	180 kg
Min Package Size	W 100 x H 30 mm	
Max Package Size	W 580 x H 820 mm	
Joint/Strap/Coil	Heat Seal/Polypropylene/ID 200 x OD 450 x W 200 mm	
Strap/Width/ Thickness	5, 6, 9, 12, 15.5 mm	
Strap Tension	784 N (80 kgf) / 450 N (46 kgf) *CE Spec.	
Power Supply	100 - 240V - Single phase 50/60Hz 0.74kVA	









01256 394444



Gordian House, Brunel Road, Houndmills Industrial Estate, Basingstoke, Hampshire RG21 6XX, UK.

