

StraPack iQ-400PLT

SEMI-AUTOMATIC STRAPPING MACHINE



- Compatible with PP strap
- Sealing Point 340mm from floor for lower pallets
- Portable design with fold up sword
- Battery/Mains or Mains only models

The iQ-400PLT is designed to economically and quickly strap most kinds of pallets using standard or heavier polypropylene strapping. The iQ-400PLT can cut the time it takes to strap pallets by up to 2/3 when compared to hand tools. Its simple operation entails pushing the track into the pallet void, pressing a button to feed the strap, and inserting the tip of the strap in the machine - and within 2 seconds your strap operation is completed. The iQ-400PLT's unique design enables to strap pallets as low as 350mm or 14". Arch track is retractable with a hand-crank. The height of the track is also adjustable to two positions depending on the type of the pallet or size of its void. For edge protection insertion, the manual mode can be selected to control strap completion.

FEATURES AND BENEFITS

Tongue in wrapping area

Manual tension or automatic tension mode can be easily selected by the operator. In manual mode, tension can be controlled via the operations bar. This is particularly helpful if corner edge protectors are being applied to the pack. In automatic mode, tension is applied at the pre-selected level.

Battery/Mains or Mains Only Mode

Two models available: iQ-400PLT (Battery/Mains) and iQ-400PLT (Mains only). Machine can be used while charging.

4-way Pallet Entry

Sword (aka bayonet) height can be adjusted easily (10 mm, 22.5 mm & 35 mm) by a lever to allow the sword to enter the pallet voids from two different directions and cross strap the pallets.

Lower Sealing Point for Small Pallets

Sealing point is only 340 mm from the floor so that can lower pallets can also be strapped.

Robust & Portable

Heavy duty metal castors allow for the machine to be quickly installed or moved to any single-phase supply outlet. Sword folds up for easy and safe storage.

Variable Tension

Range of tension settings (up to 69kg) available via a single tension dial.

Dimensions	Width	2195mm (1000 when sword is folded)
	Depth	1208 mm
	Height	542 mm
	Weight	90 kg
Sword height	10, 22.5, 35 mm	
Min package size	W 400 mm x H free	
Film roll exterior	Heat seal/ Polypropylene/ ID 200 x OD 450 x W 200 mm	
Strap width	12 mm	
Strap tension	7-69kg	
Power supply	240V1 Phase 50/60 Hz 0.65 KVA 0.4kw	

